

**POWER MANAGEMENT METHOD
FOR A PERSONAL DIGITAL ASSISTANT**

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a personal digital assistant, and in particular, to a power management method for a personal digital assistant which can be connected to an external communication terminal.

Description of the Related Art

10 A personal digital assistant (hereinafter referred to as PDA) is a multimedia device which allows one to access desired information in a desired form anytime and anywhere. The PDA has various utilities according to the user. For instance, the PDA has a personal information management (PIM) function for managing an address book, a telephone directory, a personal scheduler and memorandum. The PDA also has an additional function for gathering and exchanging information by way of facsimile or personal computer (PC) communications. Recently, the PDA may also be
15 connected with an external communication terminal, such as a portable radio telephone. If necessary, the PDA and portable radio telephone may be unified into one body.

20 When the external communication terminal and the PDA are unified, the PDA may become overloaded due to lack of power supply voltage. Therefore, there has been a demand
25 for a PDA capable of preventing the overload, even in the case where the external communication terminal is connected to the PDA.

SUMMARY OF THE INVENTION

30 It is therefore an object of the present invention to provide a power management method for preventing overload of a personal digital assistant which is connectable with an external communication terminal.

09124052.072998

09124052-072498

To achieve the above object, there is provided a power management method for a PDA (personal digital assistant) which can be connected to an external communication terminal. Upon detecting power-on of the external communication terminal, the PDA detects a battery voltage of the PDA and compares the battery voltage with a reference voltage which is slightly higher than an inoperable voltage threshold of the PDA. If the battery voltage is lower than the reference voltage, the PDA generates a low-voltage alarm message. Otherwise, if the battery voltage is higher than the reference voltage, the PDA makes a second voltage comparison between a) the difference between the battery voltage and the power required for the external communication terminal and b) the inoperable voltage threshold of the PDA. If the difference indicated in a) is larger than the voltage of b), the PDA supplies electric power to the external communication terminal.

BRIEF DESCRIPTION OF THE DRAWINGS

The above objects and other advantages of the present invention will become more apparent by describing the preferred embodiment of the present invention with reference to the attached drawings, in which:

FIG. 1 is a schematic block diagram of a personal digital assistant (PDA) which can be connected to an external communication terminal;

FIG. 2 is a flowchart for managing power of the PDA shown in FIG. 1 according to a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A preferred embodiment of the present invention will be described in detail hereinbelow with reference to the accompanying drawings. To provide a comprehensive description of the present invention, the present invention will be illustratively described, confined to the specific

embodiment, but the invention is not limited thereto. Furthermore, it should be noted that the present invention can be implemented by anyone skilled in the art with the following general description. In the description, well-known functions or constructions are not described in detail to avoid obscuring the invention.

Referring to FIG. 1, a PDA 114 includes a central processing unit (CPU) 100 for controlling an overall operation of the PDA 114 according to a control program stored in a ROM (Read Only Memory) 104. The ROM 104 stores the control program of the CPU 100, data representative of a voltage drop according to the power consumption of an external communication terminal connected to the PDA 114, and various reference data (e.g., data indicative of an inoperable voltage V_i of the PDA). A RAM (Random Access Memory) 106 temporarily stores data generated in the process of executing the control program by the CPU 100. A keypad 108 includes a plurality of numeric and function keys for generating key data to the CPU according to a key operation supplied by the user. A display 110 displays the operational status of the PDA 114 under the control of the CPU 100. A connector 112 consists of a serial port to connect the PDA 114 to the external communication terminal, and interfaces various data and control signals with the external communication terminal under the control of the CPU 100. A battery level detector 102 detects a voltage level of a battery (not shown) of the PDA 114 under the control of the CPU 100.

FIG. 2 shows a flowchart for managing the power of the PDA 114. Generally, the CPU 100 detects a voltage difference between a battery voltage V_c and a voltage drop V_e according to the power consumption of the external communication terminal. The CPU cuts off the electric power to the external communication terminal if the voltage difference is lower than the inoperable voltage threshold V_i of the PDA 114. The control flow of FIG. 2 is programmed into the ROM 104 and executed by the CPU 100.

Now, referring to FIGs. 1 and 2, if the user turns on the external communication terminal connected to the PDA 114 at step 200, the CPU 100 of the PDA 114 proceeds to step 202 to detect the battery voltage V_c by virtue of the battery level detector 102. The CPU 100 checks, at step 204, whether the battery voltage V_c is higher than a first reference voltage V_o indicative of an alarm generation voltage. The alarm generation voltage V_o is a voltage slightly higher than a threshold voltage at which the PDA 114 cannot operate normally. The alarm generation voltage V_o can be properly set according to various operating conditions of the PDA 114. If the battery voltage V_c is lower than the alarm generation voltage V_o , the CPU 100 proceeds to step 218 to generate a low-voltage alarm message through the display 110 or a speaker (not shown) and to cut off electric power to the external terminal. Thereafter, the CPU 100 checks, at step 220, whether the battery voltage V_c is lower than the inoperable voltage V_i at which the PDA 114 cannot operate normally. If the battery voltage V_c of the PDA 114 is higher than the inoperable voltage V_i , the CPU 100 ends this process. However, if the battery voltage V_c of the PDA 114 is lower than the inoperable voltage V_i , the CPU 100 sets the PDA 114 to a sleep mode in step 222. In the sleep mode, every part of the PDA 114 is inactive other than particular functions of the CPU 100, such as a power-on/off function.

However, if the battery voltage V_c is higher than the alarm generation voltage V_o at step 204, the CPU 100 proceeds to step 206 to read, from the ROM 104, a voltage drop V_e corresponding to the power consumption, or voltage drop, of the external communication terminal. The ROM 104 previously stores data corresponding to the voltage drops V_e of respective external communication terminals to be connected to the PDA 114. The CPU 100 checks, at step 208, whether a voltage difference ($V_c - V_e$) between the battery voltage V_c and the voltage drop V_e is higher than the inoperable voltage threshold V_i of the PDA. If the voltage

difference is lower than the inoperable voltage V_i , the CPU 100 proceeds to step 212 to generate an alarm message informing the user that it is impossible to power on the external communication terminal connected to the PDA 114. Subsequently, the CPU 100 checks, at step 214, whether the external communication terminal is powered off. If it is not powered off, the CPU 100 returns to step 212 to repeat the steps 212 and 214 until the user powers off the external communication terminal. If the external communication terminal is powered off at the step 214, the CPU 100 cuts off the electric power to the external communication terminal at step 216. However, if the voltage difference ($V_c - V_e$) is higher than the inoperable voltage V_i , the CPU 100 proceeds to step 210 to supply electric power to the external communication terminal and then, returns to step 202. In this way, the PDA according to the present invention can prevent the overload of the battery.

Although an illustrative embodiment of the present invention has been described herein with reference to the accompanying drawings, it is to be understood that the invention is not limited to the precise embodiment so disclosed. Various other changes and modifications may be effected by one skilled in the art without departing from the scope or spirit of the invention.